

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A sleeve for arrangement in a connector between an optical fiber and a transmitting or receiving module for optically connecting the optical fiber and the transmitting or receiving module, said sleeve comprising:

a body containing a portion defining a light-leading path of frusto-conical shape having a small-diameter end face for facing the transmitting or receiving module;

an outer tube portion disposed concentrically spaced with respect to the light-leading path and being substantially coextensive therewith; and

[[a]] an integrally formed peripheral projecting portion of said sleeve extending radially between and interconnecting the outer tube portion and the periphery of the light-leading path thereof.

Claim 2 (Original): The sleeve as set forth in claim 1, wherein

the peripheral projecting portion is circularly formed coaxially with the light-leading path,

and

the outer tube portion is cylindrically formed coaxially with the light-leading path.

Claim 3 (Previously Amended): The sleeve as set forth in claim 2, wherein
an outside diameter of the outer tube portion is substantially uniform over an entire length
of the light-leading path.

Claim 4 (Previously Amended): The sleeve as set forth in claim 1, wherein
the outer tube portion has a flange projecting annularly in a radial direction from a peripheral
surface thereof.

Claim 5 (Previously Amended): The sleeve as set forth in claim 1, including
a convex lens formed integrally with said light-leading path for extending toward the optical
fiber.

Claim 6 (Previously Amended): The sleeve as set forth in claim 5, wherein
the lens has an axial length not greater than an optical fiber side end of the outer tube portion.

Claim 7 (Previously Amended): The sleeve as set forth in claim 1, wherein
an end face of said light-leading path opposite said small diameter end face is a light-
receiving surface for receiving light transmitted by an optical fiber, and
a diameter of the light-receiving surface is larger than a diameter of a light-emitting surface
at an end face of an optical fiber.

Claim 8 (Previously Amended): The sleeve as set forth in claim 1, wherein
the small-diameter end face of the light-leading path is a light-emitting surface to emit light
transmitted to a receiving module, and
a diameter of the light-emitting surface is smaller than a diameter of a light-receiving surface
of the receiving module.

Claim 9 (Previously Amended): The sleeve as set forth in any one of claims 1-6,
wherein
the small-diameter end face of the light-leading path is a light-receiving surface for receiving
light transmitted from a transmitting module, and
a diameter of the light-receiving surface is larger than a diameter of a light-emitting surface
to the transmitting module.

Claim 10 (Withdrawn): A method of manufacturing a sleeve arranged between an optical
fiber and a transmitting or receiving module for optically connecting the optical fiber and the
transmitting or receiving module, said sleeve comprising:
a light-leading path being in a flat-headed conic shape having a small-diameter end face
facing the transmitting or receiving module;
a peripheral projecting portion projecting circularly in a radial direction from another end
portion, being on a side of the optical fiber, of the light-leading path; and

an outer tube portion extending in an optical axis direction of the light-leading path from a peripheral portion of the peripheral projecting portion toward the small-diameter end face while , covering an entire length of the light-leading path,

comprising the step of:

setting

a first metal mold having a first molding portion being along an external shape of said another end portion of the light-leading path of the sleeve and along an external shape of the outer tube portion and

a second metal mold having a second molding portion made of hard material and being along an inner surface of the outer tube portion and along a peripheral surface of the light-leading path.